

NitroX[®]

6.6KW SP HYBRID



Colorful touch LCD, IP65 protection degree



AC couple to retrofit existing solar system

16

Max. 16 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel

140

Max. charging/discharging current of 140A

6

6 time periods for battery charging/discharging



Support storing energy from diesel generator



Model		NITROX HYBRID 6.6 KW SP-5G	
Battery Input Data			
Battery Type		Lead-acid or Lithium-ion	
Battery Voltage Range (V)		40-60	
Max. Charging Current (A)		140	
Max. Discharging Current (A)		140	
Charging Strategy for Li-ion Battery		Self-adaption to BMS	
Number of Battery Input		1	
PV String Input Data			
Max. PV Input Power (W)		10560	
Max. PV Input Voltage (V)		500	
Start-up Voltage (V)		125	
MPPT Voltage Range (V)		150-425	
Rated PV Input Voltage (V)		370	
Max. Operating PV Input Current (A)		18+18	
Max. Input Short-Circuit Current (A)		27+27	
No. of MPP Trackers/ No. of Strings MPP Tracker		2/1+1	
AC Input/Output Data			
Rated AC Input/Output Active Power (W)		6600	
Max. AC Input/Output Apparent Power (VA)		7260	
Rated AC Input/Output Current (A)		30/28.7	
Max. AC Input/Output Current(A)		33/31.6	
Max. Continuous AC Passthrough (grid to load) (A)		40	
Peak Power (off-grid) (W)		2 times of rated power, 10s	
Power Factor Adjustment Range		0.8 leading to 0.8 lagging	
Rated Input/Output Voltage/Range (V)		220/230 0.85Un-1.1Un	
Rated Input/Output Grid Frequency/Range(Hz)		50/45-55, 60/55-65	
Grid Connection Form		L+N+PE	
Total Current Harmonic Distortion THDi		<3% (of nominal power)	
DC Injection Current		<0.5% In	
Efficiency			
Max. Efficiency		97.6%	
Euro Efficiency		96.5%	
MPPT Efficiency		>99%	
Equipment Protection			
Integrated		DC Polarity Reverse Connection Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Overvoltage Load Drop Protection, Ground Fault Current Monitoring, Arc Fault Circuit Interrupter (optional), Power Network Monitoring, Island Protection Monitoring, Earth Fault Detection, DC Input Switch, DC Terminal Insulation Impedance Monitoring, Residual Current (RCD) Detection, Surge protection level	
Surge Protection Level		TYPE II(DC), TYPE II(AC)	
Interface			
Communication Interface		RS485/RS232/CAN	
Monitor Mode		GPRS/WIFI/Bluetooth/4G/LAN(optional)	
General Data			
Operating Temperature Range (°C)		-40 to +60°C, >45°C Derating	
Permissible Ambient Humidity		0-100%	
Permissible Altitude		2000m	
Noise (dB)		<30	
Ingress Protection(IP) Rating		IP 65	
Inverter Topology		Non-Isolated	
Over Voltage Category		OVC II(DC), OVC III(AC)	
Cabinet Size (WxHxD mm)		340×470×258 (Excluding Connectors and Brackets)	
Weight (kg)		17.35	
Type of Cooling		Intelligent Air Cooling	
Warranty		5 Years the Warranty Period Depends on the Final Installation Site of the Inverter, More Info Please Refer to Warranty Policy	
Grid Regulation		IEC 61727,IEC 62116,CEI 0-21,EN 50549,NRS 097,RD 140,UNE 217002, OVE-Richtlinie R25, G99,VDE-AR-N 4105	
Safety / EMC Standard		IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2	

