

IPV-1K612U

Off-Grid Inverter



IPV-1K612U



High PV Input Power

1 MPP Tracker, PV Input Power up to 3200W
Max. Solar Charging Current up to 140A



High Efficiency

MPPT Efficiency $\geq 99\%$
Maximum Battery Mode Conversion Efficiency $> 93\%$



Highly User-friendly Design

Low noise performance with perfect heat dissipation
Looks like a home appliance with stunning appearance
LCD Display with physical button



Powerful Performance

110%~150% Load @ 30s
Intelligent time-of-use (TOU) mode



Solid Quality

IP54 Protection Design integrated with replaceable dust filter for harsh environmental condition
Warranty 3 years



Model	IPV-1K612U
Efficiency	
MPPT Efficiency	>99%
Max. Battery Mode Conversion Efficiency	94%
PV Input	
Max. PV Input Power (W)	3200
Max. PV Input Voltage (V)	450
Start-up Voltage (V)	30
MPPT Voltage Range (V)	35-400
Max. Input Current (A)	20
Number of MPPT	1
Number of Strings per MPPT	1
AC Input	
Nominal Input Voltage (Vac)	230
Input Voltage Range (Vac)	90-280
Max. AC Input Current (A)	9.5 (Bypass Mode)
Nominal Operating Frequency (Hz)	50/60
AC Output	
Nominal AC Output Power (W)	1600
Max. Output Apparent Power (VA)	2000
Nominal AC Output Voltage (Vac)	220/230/240 (L+N+PE)
Max. Output Current (A)	9.1
Total Current Harmonic Distortion	<3%
Nominal AC Frequency (Hz)	50/60
Surge Power (VA)	3200 @ 5s
Overload Capability	110%~150% Load @ 30s, ≥150% Load @ 5s
Battery	
Battery Type	Lead-acid/Lithium-ion/User Defined
Rated Voltage (V)	12
Battery Voltage Range (V)	10.5-15
Max. Solar Charging Current (A)	140
Max. Mains/Generator Charging Current (A)	80
Max. Discharging Current (A)	140
General	
Dimensions (L*W*H, mm)	237*305.6*100
Net Weight (kg)	5
Operating Temperature Range (°C)	-25 ~ +60 (>45°C Power Derating)
Max. Operating Altitude (m)	3000 (>2000m Power Derating)
Communication	WIFI/RS485/RS232
Diesel Generator Support	Not Support
Smart Load Support	Not Support
Parallel Capability	Not Support
Cooling Method	Intelligent Fan Cooling
Noise Level (dB)	≤50
Authentication Level	IEC62109-1, IEC62109-2, IEC61683
Protection	
Ingress Protection	IP54
Overvoltage Protection	Yes
Overload Protection	Yes
Short Circuit Protection	Yes
Over Temperature Protection	Yes
Surge Protection	DC: TYPE III; AC: TYPE III

This material is for reference only and does not constitute any commitment regarding product performance or specifications.
Product design and specifications may be changed at any time. The Company assumes no liability for any losses arising from the use of this material or the products.